



Hercules II Hybrid VERTICAL PLATFORM LIFT

ORDER / EVALUATION FORM

Date _____

Sales Rep _____

Name _____

Street _____

City _____ State _____ Zip _____

Phone _____

Fax _____

Email _____

Ref. Info _____

Account # _____

Purchase Order # _____

Ship To _____

Street _____

City _____ State _____ Zip _____

Contact _____

Phone _____

Application
 Residential - Single Family Home
 Commercial FBFL

Shipping Method
 Pick-Up Common Carrier*

Opp Ref/Project _____

Projected Close Date _____

*loading dock or a fork lift required

Model Type

750 lbs - Constant Pressure

Commercial Kit

Total Travel

Travel 0-156"

Travel 156"-180"

Travel 180"-228"

Travel 228"-276"

Travel 276"-375"

Travel higher than 375"

Number of Stops

2-stop

3-stop

4-stop

Floor to Floor Measurement

Level 1

Level 2

Level 3

Level 4

Level 5

Power Supply

24v DC / 1 HP motor

Door Configuration - Hand Swing

Left Hand Door



Right Hand Door



Pit Requirements

Standard pit is 4" *configuration with deeper pit available

Stationary ramp - (For installation without pit)


Cab Type Selection

Left Housing Machine

0° Exit



90° Exit



180° Exit



270° Exit




Right Housing Machine

0° Exit



90° Exit



180° Exit



270° Exit



Cab Size

34" x 54"

34" x 60"

36" x 54"

36" x 60"

Custom size - Max 40" x 66" or 42" x 60" _____

Hall Call Stations

Call Stations (see pictures below) QTY: _____

Position Indicator QTY: _____



1 Button
1 Keylock



Position
Indicator

Landing Doors

No Door *(Provided by Customer)*

Exterior flush mounted door: 36"W x 80"H QTY: _____

Fire rated 1.5 hr. steel flush mounted door: 36"W x 80"H QTY: _____

Wooden Interior flush mounted door: 36"W x 80"H QTY: _____

Custom dimension (max 44" width) Width: _____ QTY: _____

Spring loaded door closer
(required if you don't have a door operator) QTY: _____

Interlock Only - for customer provided door QTY: _____



Exterior Flush Door



Fire Rated Door



Interior Flush Wooden Door

Automatic Door Operators

Automatic Swing Door Operator (Residential) QTY: _____

Automatic Swing Door Operator (Commercial) QTY: _____

Handrails

Standard: 1.5" Diameter cylinder stainless steel handrail

Standard



COP - Control Operating Panel

Upgrade COP

Standard



Optional



Cab Finishes

Standard cab: Wooden melamine

Wooden Melamine: Custom color

MDF Design on wood: No color, No trim

MDF Design on wood: No color with trim

Deluxe cabs: Stainless steel

Deluxe cabs: MDF with trim - Finished

Cab Finish Examples



Standard



MDF Design on Wood



MDF Design w/ Moldures



MDF with Trim - Finished



Stainless Steel